

COMPRESSOR OIL 100

Synthetic compressor oil.
Contains atomic revitalizant.
Formulated on basis of polyalphaolefine base oils and complex of special additives.



XADO Compressor Oil 100 is universally applied for all types of compressors: rotary (including hydrovane ones), screw, single- and multi-stage reciprocating compressors; can be used in vacuum-pumps. Applied to lubricate and seal the units of low-, medium- and high-pressure compressors (0,15...50 mPa) pressing the air or gases which are insoluble in the oil.

Due to synthetic polyalphaolefine base and special additive complex XADO Compressor oil 100 extends oil drain intervals by 8 times and reduces oil evaporation by 3–4 times! Due to extremely low evaporation the oil minimizes the risk of thickening and deposits formation. Has excellent cooling and sealing properties, demulsifies water very fast.

- Compensates current wear of compressor units and protects them against wear.
- Increases efficiency of reciprocating compressors by up to 15 %.
- Increases compressor resource by 2–3 times.
- Reduces power consumption of compressor drive by up to 12%.
- Protects compressor parts from hostile environment effects.
- Decreases oil consumption for lubricating cylinder-piston group of Kreiskopfmachines.
- Ensures super-accurate adjustment of parts to each other during running-in of new compressors and after overhaul.
- Reduces and stabilizes working temperature.
- Reduces noise and vibration.

SPECIFICATIONS

ISO-VG 100
 VDL DIN 51506
 USDA H2

TECHNICAL INFORMATION

Density at 20 °C, kg/l0.874
 Viscosity at 100 °C, mm²/s12.3
 Viscosity at 40 °C, mm²/s97.0
 Viscosity index115
 Flash point, °C277
 Pour point, °C<-54

Note. Typical figures are presented.



0,5L Art. XA 22027	\$25.49
1L Art. XA 22127	\$42.49
10L Art. XA 22427	\$364.49
20L Art. XA 22527	\$694.49

Package: 0.5-20 L can; 60 and 200 L barrel.
 The delivery cost is not included.
 The prices are valid for Ebay XADO Shop
<http://stores.ebay.com/XADO-Shop>

